

Ordering Key

01US10- 24 - G5B - 20 - 102 - 0 0 0 P L 4 0 0

Input voltage	12: 12V DC 24: 24V DC 48: 48V DC
Motor and spindle type	G5A: 4500rpm / 5.08mm pitch / ACME screw G5B: 4500rpm / 5.08mm pitch / Ball screw
Gear ratio	10: 10:1 20: 20:1 40: 40:1 05: 5:1 (Ball screw only) 30: 30:1 (Ball screw only)
Stroke	102: 102mm (4") 153: 153mm (6") 203: 203mm (8") 254: 254mm (10") 305: 305mm (12") 457: 457mm (18") 610: 610mm (24")
Front connector	0: Standard
Rear connector	0: Standard
Pivot orientation of rear connector (Refer to Page 12)	0: 0° (Standard) 3: 30° 6: 60° 9: 90° C: 120° F: 150°
Positioning feedback	0: None H: Hall effect sensor x 1 P: Potentiometer (POT)
Limit switches	0: None L: Limit switches
IP level	4: IP54 (Standard) 5: IP65 9: IP66/IP69K
Option	0: None M: Manual drive socket (Refer to Page 13 for conditions to order)
Cable length	0: 250mm straight 1: 500mm straight 3: 1000mm straight 5: 1500mm straight